


# DuPont™ Cyrel® 1000 ECLF

State-of-the-Art Exposure, Light Finisher and Post Exposure Unit



[View Hi Res Image](#)

## DuPont™ Cyrel® 1000 ECLF



[View Hi Res Image](#)

## Floor Plan



Play Video



Download latest version

[DuPont Packaging Graphics](#) continues to be a global technology leader in the development and supply of flexographic printing systems. Our R&D team continues to develop innovative new solutions to help our customers expand their business by taking advantage of new and profitable opportunities in the growing flexographic packaging market. The DuPont Packaging Graphics portfolio of products includes DuPont™ Cyrel® brand photopolymer plates ([analogue](#) and [digital](#)), Cyrel® platemaking equipment, [Cyrel® round sleeves](#), [Cyrel® plate mounting systems](#) and the revolutionary [Cyrel® FAST thermal system](#).

DuPont™ Cyrel® Systems: Higher quality at high speed.

**The DuPont™ Cyrel® 1000 ECLF is designed with customer needs in mind; it is easy to install, support, maintain and operate. It is robust, extremely cost effective and reliable.**

## DuPont™ Cyrel® 1000 ECLF

### Benefits

- Maximum plate size 900 x 1,200 mm (36" x 48")
- Light integrator controlled exposure
- Clamshell design
- Outstanding vacuum draw down
- Anodised temperature controlled exposure bed
- Optimum productivity

### Product Features

DuPont™ Cyrel® 1000 ECLF can expose, post-expose and finish high quality photopolymer plates up to a format of 900 x 1,200 mm (36" x 48").

The Exposure section is a clamshell design holding 24 UV-A fluorescent tubes with built-in reflectors. One yellow control tube illuminates the exposure bed for inspection of the plate surface. Unique to this exposure unit is the anodised temperature controlled bed, closed loop system that controls the exposure bed temperature, which translates into predictable and consistent exposures. The unit is fitted with a light integrator that

compensates for the decrease in light output as the tubes age. To meet the demanding needs of high quality plates, the user can easily customise the 25 basic exposure set-ups.

Each tube is constantly monitored by a light guide, giving the operator a visual indication. There are three counters imbedded in the PLC to keep track of the number of hours the UV-A and UV-C tubes have been in operation.

The Post Exposure and Light Finisher section hold 19 UV-C and 20 UV-A tubes. The PLC allows the user to perform post exposure and finishing simultaneously. The post exposure and finisher section has 25 basic set-ups that can be easily customised by the user.

# DuPont™ Cyrel® 1000 ECLF

## State-of-the-Art Exposure, Light Finisher and Post Exposure Unit

Technical Data		
General	Details	Other Notes
<b>Equipment Name</b>	DuPont™ Cyrel® 1000 ECLF	Cooled exposure, post exposure and light finisher
<b>SAP Article Number</b>	MH74451A	
<b>Plate Thickness</b>	0.5 mm to 7.0 mm	0.019" to 0.27"
<b>Max. Nominal Plate Width</b>	900 mm (36")	
<b>Max. Nominal Plate Length</b>	1,200 mm (48")	
<b>UV-A Tubes Wave Length</b>	360 nm – 380 nm	
<b>UV-C Tubes Wave Length</b>	254 nm	
<b>Electrical (Field Configurable)</b>	370 / 440 Volt – 50 / 60 hz 208 / 240 Volt – 50 / 60 hz	3Ph / N / PE 3Ph / PE
<b>Power (nominal)</b>	10 kW	
<b>Current (Nominal Load)</b>	16 Amp @ 400 Volt; 26 Amp @ 230 Volt	
<b>Connecting Wires</b>	400 Volt configuration; 230 Volt configuration	5 x 4 mm <sup>2</sup> ; 4 x 4 mm <sup>2</sup>
<b>Grounding</b>	≤ 0.1 Ω	
<b>Exhaust (Light Finisher)</b>	Ø 140 mm (5.5")	800 m <sup>3</sup> / h (min)
<b>Environmental Data</b>	Temperature range: 17°C to 28°C (63°F to 82°F)	Relative humidity from 10% to 80% non-condensing
<b>Compressed Air Supply</b>	NA	
<b>Dimensions</b>	<b>Uncrated</b>	<b>Crated</b>
<b>L</b>	1,550 mm (61.0")	1,650 mm (65.0")
<b>W</b>	1,800 mm (70.9")	1,900 mm (74.8")
<b>H</b>	1,060 mm (41.8")	1,500 mm (59.0")
<b>H - open</b>	1,850 mm (72.9")	
<b>Weight</b>	700 kg (1,764 lbs)	970 kg (2,138 lbs)
<b>Colour</b>	DuPont Grey & DuPont Red	

For more information on DuPont™ Cyrel® or other DuPont Packaging Graphics products, please contact your local representative:

[www.cyrel.eu](http://www.cyrel.eu)

DuPont de Nemours (Deutschland) GmbH  
 DuPont Electronics & Communications  
 Hugenottenallee 175  
 63263 Neu-Isenburg  
 Germany  
 Tel: +49 (0) 6102 18 1592

DuPont (U.K.) Limited  
 DuPont Electronics & Communications  
 Wedgwood Way, Stevenage  
 Hertfordshire SG1 4QN  
 United Kingdom  
 Tel: +44 (0) 1438 73 4863