


DuPont™ Cyrel® 2000 D

State-of-the-Art Six Drawer Dryer



[View Hi Res Image](#)

DuPont™ Cyrel® 2000 D



[View Hi Res Image](#)

Floor Plan



Play Video



Download latest version

[DuPont Packaging Graphics](#) continues to be a global technology leader in the development and supply of flexographic printing systems. Our R&D team continues to develop innovative new solutions to help our customers expand their business by taking advantage of new and profitable opportunities in the growing flexographic packaging market. The DuPont Packaging Graphics portfolio of products includes DuPont™ Cyrel® brand photopolymer plates ([analogue](#) and [digital](#)), Cyrel® platemaking equipment, [Cyrel® round sleeves](#), [Cyrel® plate mounting systems](#) and the revolutionary [Cyrel® FAST thermal system](#).

DuPont™ Cyrel® Systems: Higher quality at high speed.

The DuPont™ Cyrel® 2000 D is designed with customer needs in mind; it is easy to install, support, maintain and operate. It is robust, extremely cost effective and reliable.

DuPont™ Cyrel® 2000 D

Benefits

- Maximum plate size 1,067 x 1,524 mm (42" x 60")
- Even drying temperature
- Best plate drying uniformity
- Simple to install
- Robust and easy to support
- Optimum productivity

Product Features

DuPont™ Cyrel® 2000 D is capable of drying high quality photopolymer plates up to a format of 1,067 x 1,524 mm (42" x 60"). The unit is easy to install, easy to support and maintain, simple to operate, and extremely reliable. Each of the six drawers are configured into three modules, which can be individually controlled through the touch screen control panel. This allows the choice of drying time for each drawer and the time countdown is performed second by second. This function allows the user to set the most appropriate drying time, depending on the type and thickness of the plate being used.

Consistent drying temperatures and airflow throughout the six separate drawers of the Cyrel® 2000 D ensures plate drying uniformity, and plate dimensional stability. The operator can open a dryer drawer to visually inspect the plate and determine its status anytime during operation. Automatic control (closed loop) between the temperature setting on the PLC and the heating elements prevents overheating in the drawer.

The Cyrel® 2000 D can be installed as a stand alone unit or may be combined with a Cyrel® 2000 LF. The Cyrel® 2000 D is delivered in one piece.

DuPont™ Cyrel® 2000 D

State-of-the-Art Six Drawer Dryer

Technical Data		
General	Details	Other Notes
Equipment Name	DuPont™ Cyrel® 2000 D	Six Drawer Dryer
SAP Article Number	D13450714	
Plate Thickness	0.5 mm to 7.0 mm	0.019" to 0.27"
Max. Nominal Plate Width	1,067 mm (42")	
Max. Nominal Plate Length	1,524 mm (60")	
Electrical (Field Configurable)	400 Volt – 50 / 60 hz (+10%–5%) 230 Volt – 50 / 60 hz (+10%–5%)	3Ph / N / PE 3Ph / PE
Over Current Protection	30 Amp	
Current (Nominal Load)	17 Amp @ 400 Volt 20 Amp @ 230 Volt	
Connecting Wires	400 Volt configuration 230 Volt configuration	5 x 4 mm ² 5 x 4 mm ²
Grounding	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
Noise Level	<70 dB	
Exhaust	Ø 100 mm (3.9")	165 m ³ / h–97.11 scfm to 180 m ³ / h–105.9 scfm
Environmental Data	Temperature range: 15°C to 30°C (59°F to 86°F)	Relative humidity from 40% to 60% non-condensing
Compressed Air Supply	NA	NA
Dimensions	Uncrated	Crated
D	1,530 mm (60.2")	1,760 mm (69.2")
W	2,410 mm (94.8")	2,750 mm (108.2")
H	1,080 mm (42.5")	1,450 mm (57.0")
Weight	800 kg (1,763 lbs)	1,220 kg (2,689 lbs)
Colour	DuPont Grey & DuPont Red	

For more information on DuPont™ Cyrel® or other DuPont Packaging Graphics products, please contact your local representative:

www.cyrel.eu

DuPont de Nemours (Deutschland) GmbH
 DuPont Electronics & Communications
 Hugenottenallee 173 – 175
 63263 Neu-Isenburg
 Germany
 Tel: +49 (0) 6102 18 4400

DuPont (U.K.) Limited
 DuPont Electronics & Communications
 Wedgwood Way, Stevenage
 Hertfordshire SG1 4QN
 United Kingdom
 Tel: +44 (0) 1438 73 4863