

DuPont™ Cyrel® FAST Round FR 1450

Solvent-Free, Flexographic Sleeve Processor



business by taking advantage of new and profitable opportunities in the growing flexographic packaging market. The DuPont Packaging Graphics portfolio of products includes DuPont[™] Cyrel[®] brand photopolymer plates (analogue and digital), Cyrel[®] platemaking equipment, Cyrel[®] round sleeves, Cyrel[®] plate mounting systems and the revolutionary Cyrel[®] FAST thermal system.

The DuPont" Cyrel® FAST Round FR 1450 is designed with customer needs in mind; it is easy to install,


DuPont Packaging Graphics continues to be a global technology leader in the development and supply of flexographic

printing systems. Our R&D team continues to develop innovative new solutions to help our customers expand their

DuPont™ Cyrel® Systems: Higher quality at high speed.

Dui ont Cyrei Systems. Higher quality at high speed

DuPont™ Cyrel® FAST Round FR 1450



support, maintain and operate. It is robust, extremely cost effective and reliable.

DuPont™ Cyrel® FAST Round FR 1450

Benefits

- Maximum sleeve size 1,450 x 1,000 mm (57" x 39")
- Extremely rapid access time
- Smaller environmental footprint
- High-quality precision printing
- Higher durability for long print runs
- Robust and easy to support
- Optimum productivity
- Small equipment footprint

Floor Plan



Product Features

DuPont™ Cyrel® FAST Round FR 1450 is a sleeve making system that uses dry, thermal technology to process high quality photopolymer sleeves, thus eliminating all solvents and aqueous solutions from the plate room.

The Cyrel® FAST Round FR 1450 allows the production of 4–5 Cyrel® FAST round seamless photopolymer sleeves at a typical format of 1,450 x 500 mm (57" x 39") in less than one hour, making it the ideal just-in-time sleeve making system for a market.

The Cyrel® FAST Round FR 1450 delivers outstanding sleeve quality and uniformity. This processor has the ability to produce a finished sleeve without solvent washout. The new round exposure equipment (Cyrel® FAST Round EX 1450 and LF 1450) for exposing and light-finishing sleeves is available to complement the Cyrel® FAST Round FR 1450 as an all-round system solution. As with all elements of the Cyrel® FAST round system, it is environmentally friendly with no solvents to handle, store or recycle and no drying equipment is required. In addition, the new design saves space and requires no expensive plate room construction.

The technology enhances the production of high quality sleeves quickly, by combining the efficiency and speed of digital sleeve imaging with the productivity and environmental benefits of dry, thermal sleeve processing.

The digital sleeves for DuPont's thermal sleeve making process are designed to meet the needs of high quality plates with fine halftone, line-work and solids.



Download latest version



DuPont™ Cyrel® FAST Round FR 1450

Solvent-Free, Flexographic Sleeve Processor

| Technical Data | | |
|---------------------------------|---|--|
| General | Details | Other Notes |
| Equipment Name | DuPont [™] Cyrel® FAST Round FR 1450 | Thermal developer (water cooled) |
| SAP Article Number | D14466719 | |
| Max. Nominal Sleeve Width | 1,450 mm (57") | |
| Min. Nominal Sleeve Width | 300 mm (11.8") | |
| Max. Nominal Sleeve Repeat | 1,000 mm (39.3") | |
| Min. Nominal Sleeve Repeat | 330 mm (12.9") | |
| Sleeve Thickness | Thin 1,573 mm/Classic 3,165 mm | |
| Electrical (Field Configurable) | 3 x 400 V + N, 10% | |
| Power (Nominal) | 24 kW | |
| Current (Nominal Load) | 35 A | |
| Grounding | | |
| Exhaust | Ø 250 mm (9.05") | 1,200 m³ / h-706.3 ft³ scfm (min) |
| Environmental Data | Temperature range: 18°C to 27°C (65°F to 80°F) | Relative humidity from 20% to 80% non-condensing |
| Compressed Air Supply | 6.2 bar, 300 l/min | |
| Dimensions L D H | Uncrated 3,360 mm (132.3") 1,460 mm (57.5") 1,970 mm (77.6") | Crated 4,100 mm (161.4") 1,900 mm (74.8") 2,400 mm (94.5") |
| Weight | 4,000 kg (7,716 lbs) | 5,700 kg (8,818 lbs) |
| Colour | DuPont Grey & DuPont Red | |

www.cyrel.eu

For more information on DuPont" Cyrel® or other DuPont Packaging Graphics products, please contact your local representative:

DuPont de Nemours (Deutschland) GmbH DuPont Electronics & Communications Hugenottenallee 175 63263 Neu-Isenburg Germany Tel: +49 (0) 6102 18 1592 DuPont (U.K.) Limited DuPont Electronics & Communications Wedgwood Way, Stevenage Hertfordshire SG1 4QN United Kingdom Tel: +44 (0) 1438 73 4863